

isolcork
Since 2010



RUBBER TOP

Membrana de caucho - Membrane recyclée

**WATERPROOFING MEMBRANE
FOR ROOFS AND TERRACES**



**BASED ON RECYCLED
RUBBER PARTICLES**

33 LBS

INSTRUCTIONS FOR USE

1. The surface must be clean, dust free and dry.
2. Pour the content of the bag on a hod.
3. Beat with the help of helical-tip mixer at high speed for at least 2 or 3 minutes until a homogeneous dough mixture is obtained.
4. In case of coloured membrane, pour the colourant and stir the mixture again.
5. Apply the mixture by spraying with an air compressor (minimum pressure 5.0 bar) and a hopper gun with a No 6 nozzle to achieve a uniform coat.
6. After 24 hours of drying, apply a second coat of the product.
7. The tools can be cleaned with water before drying.
8. The ambient temperature should be between 41°F to 95° F.
9. Coverage : 21.5 ft2 per gallon after 2 coats. 118.4 ft2 per 5 gallon after 2 coats. Performance may vary depending on wind conditions.
10. Application thickness : 0.098 to 0.118 inch in 2 coats.

SPECIFICATIONS

Appearance : granulate
 Finishing texture : Rough
 Color : Standard black
 Presentation : 5 Gl with 33 Lbs

SAFETY

Non-flammable product
 Non-toxic product
 Does not contain solvents
 Recycled product from vehicle tires
 Keep container tightly closed
 Keep away from children
 Do not ingest

COMPOSITION

Mix of recycled rubber particles with additives.

STORAGE

The product should be stored in well ventilated areas, protected from sunlight, water and frost, at temperatures between +41° F and +86° F.
 Storage time: 12 months from manufacture date.

FIRST AID MEASURES

SITUATION	ACTION
Contact with eyes	Wash with water for 15 minutes and consult a doctor
Contact with skin	Remove clothing or footwear contaminated. Wash with water and soap
After ingestion	Do not induce vomiting. Clarify the mouth with water. Consult a doctor

ISOLCORK TEXAS
 1801 MAIN ST. SUITE 1300
 HOUSTON, TX 77002
 PHONE: 1 (832) 606 5837
 EMAIL: TEXAS@ISOLCORK.COM

ISOLCORK ARIZONA
 5541 LAMPLIGHTER DR. TUCSON,
 85746, TUCSON, AZ
 PHONE: 1 (520) 867 5400
 MAIL: ARIZONA@ISOLCORK.COM

MANUFACTURED IN CHILE

ISOLCORK S.P.A
 CAMINO LO ECHEVERS 280 #10, QUILICURA,
 SANTIAGO - CHILE
 CHILE@ISOLCORK.COM

DISTRIBUTED BY:

ISOLCORK ARGENTINA - ARGENTINA@ISOLCORK.COM
 ISOLCORK BRASIL - ATENDIMENTO@ISOLCORK.COM.BR
 MASISA COLOMBIA - ISOLCORK@MASISA.COM
 ISOLCORK ECUADOR - ECUADOR@ISOLCORK.COM
 ISOLCORK MEXICO - MEXICO@ISOLCORK.COM



CONTINUOUS WATERPROOFING MEMBRANE, THAT REACHES ALL SPACES.

VERY GOOD RESISTANCE TO TEARING DOES NOT DETERIORATE WHEN EXPOSED TO ULTRAVIOLET SUNLIGHT.

DOES NOT LOSE FLEXIBILITY AT LOW OR HIGH TEMPERATURES.

CAN BE USED TO REPAIR DETERIORATED AND CRACKED ASPHALT MEMBRANES AND SHINGLES DUE TO SUN EXPOSURE.

SELF-EXTINGUISHING UNDER FIRE ACTION

ANTI - SLIP.

Please Scan the QR Code for more information.



ELIMINATES THE NEED TO HANDLE HEAVY ROLLS.

ALLOWS THE APPLICATION OF OTHER FINISHING MATERIALS SUCH AS SPRAY CORK, OR FINISHES WITH MORTAR AND / OR CERAMIC FLOORING.

POSSIBILITY OF APPLICATION ON VERTICAL WALLS AS A SHEET FOR STEAM OR WATERPROOFING.

ADHESION ON ALL TYPES OF MATERIALS:
 ADHESION ON ALL TYPES OF MATERIALS: TRADITIONAL MORTAR, CONCRETE, BRICKS, CORRUGATED STEEL SHEET, WOOD, PVC, ASPHALT TILES, CERAMICS, EXPANDED POLYSTYRENE, EXTRUDED POLYSTYRENE, SINGLE LAYER MORTAR, ON EXTERIOR AND INTERIOR WALLS, PLASTER AND PLASTER BOARD ON INTERIOR WALLS, FIBER CEMENT.

isolcork
 Since 2010

